

THE PREMIUM DEVICE FOR STEEP-SLOPE ROOFING SAFETY



An Adjustable Roofing Anchor and a "First-Man-Up/Last-Man-Down" System All In One.

FEATURES

- ◆ Etched pitch-grid allows user to customize 6/12 to 12/12 pitch selection
- ◆ Innovative arch straddles ridge vent when installing
- ◆ Exceeds industry standard of 5,000-pound tensile strength (when anchored)
- ◆ Integrated rope-and-harness connection capabilities
- ◆ Constructed from solid, aircraft-grade aluminum
- ◆ Four, pre-drilled holes for anchoring
- ◆ Adjustable, pitch-specific settings to maximize contact between The RIDGEPRO™ and the peak

BENEFITS

- ◆ Connect to the peak before stepping onto a steep-slope roof
- ◆ Safely transition on and off ladders from 6/12 to 12/12 pitches
- ◆ Faster access to the peak than standard rope-and-harness techniques
- ◆ Lightweight alternative to bulky scaffolding or roof planks
- ◆ Versatility across many professional roofing applications
- ◆ Easy to assemble and install



THE PREMIUM DEVICE FOR STEEP-SLOPE ROOFING SAFETY

SPECIFICATIONS	
Material Type:	6061-T6 Aluminum
Net Weight:	7.0 lbs. / 3.18 kg.
Max Dimensions (LWH):	In: 25.38 x 10 x 13.25 Cm: 64.45 x 25.4 x 33.66
Weight Load:	Anchored: >5000lbs. / >2268 kg. Not anchored: 310lbs. / 141 kg.
Colors:	Yellow and Red
Part No.	RP3Q14-R
Description:	An adjustable roofing anchor and first-man-up safety device for vertical and horizontal movement. Safety equipment.

Parent Company: Strawder Family Innovations, LLC

Corporate Headquarters: 20 Commerce Drive, Suite 135, Cranford, NJ 07016 USA

Customer Service: 1-908-603-6266 Support@theridgepro.com

Website: www.theridgepro.com



The RIDGEPRO™ is a registered trademark.

Not affiliated with or endorsed by Ridge Tool Company or RIGID, Inc.