



# 365 RUBBERIZED FLASHING CEMENT

## TECHNICAL DATA SHEET



### DESCRIPTION:

**APOC 365 Rubberized Flashing Cement** is an extremely flexible, highly durable, long-lasting leak-repair designed to be applied in all-weather/seasons and in wet or dry applications. It can be used for patching splits, cracks, and seams in spudded gravel, mineral surfaced cap sheet and smooth surface asphalt roofs, as well as composition shingle roofs as well as vertical applications. APOC 365 seals around chimneys, vent pipes, gravel guards, down spouts, cracks in concrete and more. APOC 365 exceeds performance requirements of ASTM D3409 and ASTM D4586, TYPE I and is Miami-Dade County Product Control Approved.

### PREPARATION:

All surfaces must be clean and free of surface rust, dust and any other foreign matter or debris. For longevity and UV protection, it is recommended to protect repairs with the application of a reflective coating after they have cured for 30-90 days. Not for use on single ply membranes.

### APPLICATION:

For easier application, apply when surface temperatures are between 0°F (-17°C) and 120°F (48°C). In colder weather, product should be stored at ambient temperatures 65°F (18°C) to 80°F (26°C) at least 24 hours prior to application. Apply with a trowel or putty knife. Work material to an even consistency over and into the area to be repaired. Apply cement 1/8" thick, two or three inches beyond the problem area. Next, reinforce the repair by embedding a layer of APOC reinforcing fabric into the repair. Brush fabric into cement ensuring it is fully saturated from the bottom side up. Finally, cover the fabric with an additional layer of cement. Form a feathered edge with cement where chimneys, vent pipes and other projections meet the roof line. Exterior use only.



### CLEAN-UP:

Tools are best cleaned with xylene, but paint thinner, mineral spirits or a citrus degreaser may be used.

### PRECAUTIONS:

Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not eat, drink or smoke when using this product. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist/vapors/spray. Wear protective gloves, protective clothing, eye protection and face protection. Use in a well-ventilated area. Avoid release to the environment. Wash all exposed external body areas thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. KEEP OUT OF REACH OF CHILDREN. Contains bitumen, white spirits, crystalline silica, titanium dioxide and other solvents and additives. If exposed or concerned get medical advice. IF SWALLOWED Immediately call a POISON CENTER/doctor/physician/first aider. Do NOT induce vomiting. IF INHALE Remove person to fresh air and keep comfortable for breathing. IF ON SKIN: Wash with plenty of soap and water. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of fire: Use alcohol resistant foam or normal protein foam to extinguish. Collect spillage. Take off contaminated clothing and wash it before reuse. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Dispose of contents/container to authorized hazardous or special waste collection point and in accordance with applicable local/national/regional/international regulations. SEE SAFETY DATA SHEET.



### TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS:

Weight Per Gallon	8.5 - 9.0 lb.
Adhesion Underwater	Excellent
Application Temperatures	40°F - 120°F

### Approx. Shipping Weights:

(Note: All approx. weights include container)

10 fl. oz. tube (296 mL)	1 lb.
1 gallon (3.8L)	10 lb.
(4) 1 gallon containers/case	41 lb.
3 gallons (13.2 L)	33 lb.

VOC: <250 g/L (regulatory)

Gardner-Gibson, Inc.

4161 East 7th Avenue. Tampa, FL 33605  
1.800.237.1155 | www.icpgroup.com | D23



### PERSONAL PROTECTIVE EQUIPMENT



EYEWEAR



PROTECTIVE CLOTHING



GLOVES

### STORAGE & HANDLING PRECAUTIONS:

When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure on top of 6 mil plastic sheeting to prevent damage due to accidental spills or loosening of lids. Do not store at temperatures above 110°F (43°C). Storage of materials should be in a cool, shaded area during hot weather. For ease of application, store as close as possible to ambient temperatures during cold weather. Tightly seal container when not in use. This will help slow material evaporation, keep moisture out and preserve the product. Storing outdoors or in warm temperatures will significantly reduce shelf life.

### WARRANTY AND DISCLAIMER:

APOC warrants product to be free of material defects for a period of 10 years, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper preparation and drying conditions must be observed to achieve correct results. Should a product not perform as stated, APOC shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product to repair the affected area or prorate a portion of the purchase price of the defective product based on the claim period. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY APOC TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.